


**INDICATORE
INDICATOR
ANZEIGEGERÄT**

SPECIFICHE TECNICHE – TECHNICAL SPECIFICATION – TECHNISCHE SPEZIFIKATION

Alimentazione Power supply Stromversorgung	A batterie completo di caricabatteria With batteries complete with charger Mit Batterien inklusive Ladegerät		
Assorbimento massimo Maximum power consumption Maximaler Stromverbrauch	1,5 W (ogni SLIM) 1.5 W (each SLIM) 1,5 W (je SLIM)	Isolamento Insulation Isolierung	Classe III Class III Klasse III
Temperatura di funzionamento Operating temperature Betriebstemperatur	-10 °C / + 50 °C 14 °F / 122 °F	Umidità Humidity Luftfeuchtigkeit	Massimo 85% senza condensa Maximum 85% non-condensing Maximal 85% nicht kondensierend
Display	Numerico a 5 cifre LED rossi a 7 segmenti (h 10 mm) 5-digit numeric red 7-segment LEDs (h 10 mm) 5-stellige numerische rote 7-Segment-LEDs (h 10 mm)		
Tastiera Keyboard Tastatur	3 pulsanti meccanici 3 mechanical keys 3 mechanische Tasten		
Ingresso celle di carico Load cell input Eingang Wägezellen	Massimo 2 celle da 350 Ω in parallelo (o 4 celle da 700 Ω) Maximum 2 cells of 350 Ω in parallel (or 4 cells of 700 Ω) Maximal 2 Zellen mit 350 Ω parallel (oder 4 Zellen mit 700 Ω)		
Linearità Linearity Linearität	< 0,01% del fondo scala < 0.01% of full scale < 0,01% des Skalenendwertes	Deriva in temperatura Temperature deviation Temperaturabweichung	< 0,001% del fondo scala/°C < 0.001% of full scale/°C < 0,001% des Skalenendwertes/°C
Risoluzione interna Internal resolution Interne Auflösung	24 bit	Campo di misura Measuring range Messbereich	Da -3,9 mV/V a +3,9 mV/V From -3.9 mV/V to +3.9 mV/V Von -3,9 mV/V bis +3,9 mV/V
Filtro digitale Digital filter Digitalfilter	Selezionabile 0,1 Hz – 50 Hz Selectable 0.1 Hz – 50 Hz Wählbar 0,1 Hz – 50 Hz	Numero decimali peso Weight decimals Dezimalstellen Gewicht	Da 0 a 3 cifre decimali From 0 to 3 decimals Von 0 bis 3 Dezimalstellen
Taratura di zero e fondo scala Calibration zero and full scale Kalibrierung Null und Endwert	Eseguitabile da pulsanti Executable through keys Über Tasten ausführbar	Controllo interruzione cavi cella Cell cables interruption check Unterbrechungskontrolle Zellkabel	Sempre presente Always present Immer präsent
Memoria codice programma Program code memory Kodespeicher Programm	32 kByte	Memoria dati Data memory Datenspeicher	2 kByte
Conformità alle Normative Compliance to norms Normen-Konformität	EN61000-6-2, EN61000-6-3, EN61010-1		

DIMENSIONI – DIMENSIONS – ABMESSUNGEN

Dimensioni ingombro valigetta Overall dimensions of the case Gesamtabmessungen des Koffers	260 x 250 x 125 mm 10.2 x 9.8 x 4.9 in
--	---

CONNESSIONI – CONNECTIONS – ANSCHLÜSSE
